



# The Metallurgical Examination and Inspection of Apache Tail Rotor Strap Pack Laminates and Assemblies

by Scott M. Grendahl

ARL-TR-2018

July 1999

19990916 008

Approved for public release; distribution is unlimited.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

# **Army Research Laboratory**

Aberdeen Proving Ground, MD 21005-5069

---

---

ARL-TR-2018

July 1999

---

## **The Metallurgical Examination and Inspection of Apache Tail Rotor Strap Pack Laminates and Assemblies**

Scott M. Grendahl

Weapons and Materials Research Directorate, ARL

---

## **Abstract**

---

The U.S. Army Research Laboratory-Weapons and Materials Research Directorate (ARL-WMRD) performed a dimensional inspection and metallurgical investigation of AH-64 Apache tail rotor strap pack assemblies and individual laminate sets. All of the dimensional critical characteristics were examined in an attempt to determine the cause of a buckling phenomenon within the strap pack assemblies. Conformance to the manufacturer's governing specifications with respect to the material, heat treatment, and marking requirements was also investigated. The cause of the buckling was attributed to a combination of factors. Dimensional nonconformances were identified. Most of the hole diameters were found to be well below the specified range, causing the assemblies to be forced together. Transposition of the laminates during manufacture was also highly likely to have occurred, adding to the misalignment of the assembly. All other characteristics of the laminates and assemblies were found to conform to the governing part drawings and specifications.



## **Acknowledgments**

The author would like to thank Mr. Victor K. Champagne and Mr. Marc S. Pepi of the U.S. Army Research Laboratory (ARL), Weapons and Materials Research Directorate (WMRD), Aberdeen Proving Ground (APG), MD, for fruitful discussions concerning this endeavor. Additionally, the author would like to acknowledge Mr. James Catalano, ARL, APG, MD, and Mr. Andrew Beaupre of the Worcester Polytechnic Institute, Worcester, MA, for their data contributions to this work.

INTENTIONALLY LEFT BLANK.

# Table of Contents

	<u>Page</u>
<b>Acknowledgments.....</b>	iii
<b>List of Figures .....</b>	vii
<b>List of Tables .....</b>	ix
<b>1. Introduction .....</b>	1
<b>2. Objectives .....</b>	1
<b>3. Experimental Procedure.....</b>	2
3.1 Visual Inspection and Light Optical Microscopy.....	2
3.2 Dimensional Inspection.....	5
<b>4. Discussion.....</b>	6
<b>5. Metallography.....</b>	15
<b>6. Conclusions .....</b>	18
<b>7. References .....</b>	19
<b>Appendix A: Edge Break Data for Strap Pack 0899.....</b>	21
<b>Appendix B: Edge Break Data for Strap Pack 1548.....</b>	45
<b>Appendix C: Edge Break Data for Strap Pack 1174.....</b>	69
<b>Appendix D: Edge Break Data for Randomly Selected Strap Pack Laminates From Packs 1167–1177 and Two “Extra” Laminates.....</b>	93
<b>Distribution List .....</b>	121
<b>Report Documentation Page.....</b>	123

INTENTIONALLY LEFT BLANK.

## List of Figures

<u>Figure</u>	<u>Page</u>
1. Macrograph of the As-Received Strap Pack 1548 (Top View).....	2
2. Macrograph of the As-Received Strap Pack 1548 (Side View) .....	3
3. Macrograph of the As-Received Strap Pack 0899 (Top View).....	4
4. Macrograph of the As-Received Strap Pack 0899 (Side View) .....	4
5. Macrograph of the Buckling on Strap Pack 1548 .....	5
6. Illustration of the Measurement Inaccuracy Due to Edge Finishing .....	6
7. Illustration of the Defined Laminate Dimensions for Tables 1, 2, 3, and 4 .....	8
8. Illustration of the Transposition About the Y-Axis and Buckling Scenario .....	9
9. Micrograph of a Longitudinal Section of 1548 .....	16
10. Micrograph of a Longitudinal Section of 0899 .....	16
11. Micrograph of a Transverse Section of 1548 .....	17
12. Micrograph of a Transverse Section of 0899 .....	17

INTENTIONALLY LEFT BLANK.

## List of Tables

<u>Table</u>	<u>Page</u>
1. Dimensional Data for QDR Exhibits 1548 and 0899.....	7
2. Dimensional Data for Randomly Selected Individual Laminate Sets and Odd Laminates .....	10
3. Dimensional Data for the Holes and Radii of Randomly Selected Laminates.....	11
4. Dimensional Examination of Laminate Set 1174 .....	12

INTENTIONALLY LEFT BLANK.



# **1. Introduction**


The U.S. Army Aviation and Missile Command (AMCOM) requested an investigation consisting of metallurgical examination and dimensional inspection of Apache tail rotor strap pack assemblies and individual laminate sets. The laminate material is very thin (approximately 0.014 in) sheet AM-355, a semiaustenetic stainless steel. The U.S. Army Research Laboratory, Weapons and Materials Research Directorate (ARL-WMRD), received two Quality Deficiency Report (QDR) exhibits, which were to be used as the assemblies for inspection. Additionally, nine individual laminate sets were sent to ARL-WMRD for inspection (serial numbers [SN] 003343-1167, -1168, -1169, -1172, -1173, -1174, -1175, -1176, and -1177). ARL-WMRD was requested to perform a dimensional inspection of the two QDR assemblies per the governing specifications and also verify that they were properly assembled. Additionally, ARL-WMRD was requested to inspect three laminates (selected at random) from each separate laminate set received for conformance to the governing documents. Later, this was altered to include a complete dimensional inspection of one laminate set selected at random. Verification of surface finish, edge finish, and hole finish and all other critical characteristics was to be determined as prescribed by the governing documents. ARL-WMRD was also requested to perform a full metallurgical investigation of one laminate from both QDR assemblies received to verify material and heat treatment. Finally, it was requested of ARL-WMRD to substantiate that all components were marked and designated in accordance with the appropriate specifications.

## **2. Objectives**

The purpose of this work was to determine the cause of the buckling phenomenon on the two QDR tail rotor assembly exhibits. Additionally, all components involved were evaluated for conformance to the governing manufacturing, process, and identification specifications of the assembly.


### 3. Experimental Procedure

**3.1 Visual Inspection and Light Optical Microscopy.** Both QDR exhibits (designated W81CL8940027 for SN 003343-0899 and W81CL8940085 for SN 003343-1548) received by ARL-WMRD were visually inspected [1, 2]. It was noted that both exhibits experienced extensive buckling between the individual laminates that make up the assemblies. The assembly is governed by the McDonnell Douglas drawing package BP-7-211421035 [3]. Figures 1 and 2 depict QDR exhibit 003343-1548 (1548) as received by ARL-WMRD.




**Figure 1. Macrograph of the As-Received Strap Pack 1548 (Top View). (Scale in Inches.)**

Figures 3 and 4 show QDR exhibit 003343-0899 (0899) as received by ARL-WMRD. The individual quality deficiency reports designate buckling and/or displacement of the first laminate for exhibit 1548 and the third and eleventh laminate for exhibit 0899. These findings were verified by ARL-WMRD via optical microscopy. The first laminate was visibly buckled on exhibit 1548, as depicted in Figure 5. Closer examination of the white outlined box in Figure 4 reveals the buckling of the third and eleventh laminates on exhibit 0899. The additional nine




**Figure 2. Macrograph of the As-Received Strap Pack 1548 (Side View). (Scale in Inches.)**


laminate sets received by ARL-WMRD were also inspected for surface finish and marking requirements per EPB-4-321, Rev. E [4]. All components had surface finishes well within specification. The individual laminates had surface finishes ranging from 2-4 Ra ( $\mu\text{m}$ ), well within the specified value of 8 Ra ( $\mu\text{m}$ ). The laminates are governed by the McDonnell Douglas laminate drawing package, BP-7-211421023 and the AM-355 material specification, HMS-6-1073, Rev. E [5, 6]. All tail rotor laminates were blanked within  $15^\circ$  of the longitudinal grain direction of the components in agreement with EPB-4-321, Rev. E [4]. The components were also correctly marked and/or stamped according to the governing identification and serialization specifications, HP 8-5 and HP 8-8 [7, 8].



**Figure 3. Macrograph of the As-Received Strap Pack 0899 (Top View). (Scale in Inches.)**




**Figure 4. Macrograph of the As-Received Strap Pack 0899 (Side View). (Scale in Inches.)**



**Figure 5. Macrograph of the Buckling on Strap Pack 1548. (Scale in Inches.)**

**3.2 Dimensional Inspection.** A three-axis coordinate measuring machine (CMM) was used to check the dimensional conformity of the strap pack laminates. It must be understood in an analysis of the data that the laminates were edge-finished prior to dimensional inspection. This is significant, since the CMM employs a spherical ruby stylus when acquiring measurement data. If the edges of the laminates are also rounded, slight inaccuracies may exist in the measurements obtained due to the extreme thinness of the laminates (approximately 0.014 in). Figure 6 illustrates this phenomenon. However, it is important to note that this small source of error would not account for hole dimensions with measured value smaller than that specified, as the drawing illustrates. If the spherical stylus caused error to be introduced, the dimensions of the holes would be artificially inflated rather than reduced. Therefore, the slight inaccuracy might only explain dimensions that are out of tolerance by being larger than specified. Dimensions found to be smaller than specified cannot be explained away under this argument and are of significant concern. This inaccuracy in measurement due to the edge finishing and spherical stylus is very small, approximately 0.0005 in maximum, and is exaggerated in Figure 6.



**Figure 6. Illustration of the Measurement Inaccuracy Due to Edge Finishing.**

Table 1 is a listing of the measurements taken by the CCM during the inspection of the QDR exhibit tail rotor strap pack assemblies, 1548 and 0899. Refer to the laminate illustration, Figure 7, for the individual measurement locations.


## 4. Discussion

The boxed data in Table 1 indicate the most likely source of the buckling. It can be seen from the data for dimensions E and F that the average value of DIM. E is larger by 0.006 in (average value DIM. E = 1.1294 in and average value DIM. F = 1.1233 in, neglecting the boxed data). The transposition occurs when a laminate is rotated 180° and inserted back into the stack. Therefore, DIM. E becomes DIM. F for the transposed laminate. It can be seen in the data that the transposed laminate's DIM. E values closely resemble the other laminate's DIM. F values.

**Table 1. Dimensional Data for QDR Exhibits 1548 and 0899**

Laminate	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F	HOLE 1	HOLE 2	HOLE 3	HOLE 4
Specification	23.200	11.600	11.600	2.250	1.125	1.125	0.6883	0.6883	0.1955	0.1955
Tolerance	± 0.010	± 0.010	± 0.010	± 0.010	± 0.010	± 0.010	+ 0.0002 - 0.0003	+ 0.0002 - 0.0003	± 0.0005	± 0.0005
#1548 - 1	23.20456	11.60183	11.60272	2.25099	1.12874	1.12225	0.68314	0.68443	0.19135	0.19213
#1548 - 2	23.20537	11.60260	11.60276	2.25192	1.12187	1.13005	0.68486	0.68523	0.19210	0.19622
#1548 - 3	23.20522	11.60138	11.60384	2.25078	1.11997	1.13080	0.68531	0.68611	0.19266	0.19195
#1548 - 4	23.20614	11.60289	11.60325	2.25194	1.12089	1.13105	0.68582	0.68586	0.19331	0.19233
#1548 - 5	23.20673	11.60381	11.60292	2.25018	1.12116	1.12901	0.68625	0.68350	0.19139	0.19238
#1548 - 6	23.20611	11.60287	11.60324	2.25046	1.11985	1.13062	0.68531	0.68760	0.19168	0.19322
#1548 - 7	23.20587	11.60316	11.60271	2.25145	1.12176	1.12969	0.68687	0.68330	0.19110	0.19196
#1548 - 8	23.20560	11.60240	11.60320	2.25260	1.12170	1.13090	0.68520	0.68500	0.19290	0.19220
#1548 - 9	23.20480	11.60250	11.60230	2.25030	1.12100	1.12930	0.68590	0.68520	0.19470	0.19380
#1548 - 10	23.20700	11.60290	11.60420	2.24930	1.11930	1.12990	0.68630	0.68580	0.19340	0.19360
#1548 - 11	23.20600	11.60310	11.60290	2.25090	1.12210	1.12980	0.68580	0.68600	0.19400	0.19290
#1548 - 12	23.20550	11.60280	11.60260	2.25230	1.12240	1.12990	0.68530	0.68570	0.19290	0.19140
#1548 - 13	23.20590	11.60310	11.60280	2.25130	1.12170	1.12950	0.68710	0.68640	0.19390	0.19390
#1548 - 14	23.20570	11.60310	11.60260	2.25150	1.12120	1.13030	0.68590	0.68570	0.19360	0.19290
#1548 - 15	23.20680	11.60330	11.60350	2.25160	1.12150	1.13010	0.68680	0.68720	0.19480	0.19370
#1548 - 16	23.20570	11.60290	11.60280	2.25070	1.12120	1.12940	0.68570	0.68600	0.19320	0.19320
#1548 - 17	23.20610	11.60290	11.60320	2.25180	1.12190	1.12990	0.68780	0.68800	0.19490	0.19430
#1548 - 18	23.20600	11.60290	11.60320	2.25060	1.12140	1.12990	0.68740	0.68730	0.19440	0.19370
#1548 - 19	23.20620	11.60290	11.60330	2.25180	1.12240	1.12920	0.68740	0.68630	0.19440	0.19340
#1548 - 20	23.20530	11.60250	11.60280	2.25200	1.12150	1.13050	0.68680	0.68570	0.19400	0.19420
#1548 - 21	23.20620	11.60290	11.60330	2.25050	1.12120	1.12930	0.68600	0.68690	0.19310	0.19250
#1548 - 22	23.20570	11.60290	11.60280	2.25120	1.12180	1.12930	0.68540	0.68680	0.19270	0.19210
#0899 - 1	23.20560	11.60270	11.60290	2.25170	1.12840	1.12320	0.68770	0.68740	0.19500	0.19470
#0899 - 2	23.20600	11.60290	11.60320	2.25250	1.12940	1.12300	0.68780	0.68760	0.19480	0.19470
#0899 - 3	23.20540	11.60270	11.60260	2.25220	1.12280	1.12940	0.68710	0.68750	0.19630	0.19580
#0899 - 4	23.20560	11.60270	11.60290	2.25190	1.1289	1.12300	0.68710	0.68680	0.19530	0.19500
#0899 - 5	23.20460	11.60210	11.60250	2.25220	1.12860	1.12350	0.68730	0.68730	0.19480	0.19400
#0899 - 6	23.20560	11.60240	11.60320	2.25220	1.12860	1.12360	0.68700	0.68700	0.19540	0.19500
#0899 - 7	23.20530	11.60240	11.60290	2.25220	1.12880	1.12350	0.68740	0.68740	0.19530	0.19570
#0899 - 8	23.20550	11.60290	11.60290	2.25280	1.12940	1.12340	0.68710	0.68670	0.19410	0.19460
#0899 - 9	23.20540	11.60260	11.60270	2.25230	1.12920	1.12310	0.68720	0.68760	0.19530	0.19570
#0899 - 10	23.20520	11.60250	11.60280	2.25150	1.12880	1.12270	0.68730	0.68730	0.19490	0.19410
#0899 - 11	23.20560	11.60280	11.60280	2.25360	1.12300	1.13060	0.68840	0.68840	0.19430	0.19470
#0899 - 12	23.20570	11.60290	11.60280	2.25270	1.12950	1.12320	0.68660	0.68660	0.19490	0.19440
#0899 - 13	23.20550	11.60250	11.60300	2.25300	1.12960	1.12340	0.68730	0.68720	0.19530	0.19450
#0899 - 14	23.20500	11.60250	11.60250	2.25310	1.12940	1.12360	0.68670	0.68660	0.19440	0.19440
#0899 - 15	23.20520	11.60260	11.60260	2.25310	1.12950	1.12350	0.68730	0.68630	0.19470	0.19420
#0899 - 16	23.20500	11.60250	11.60250	2.25280	1.12960	1.12330	0.68790	0.68740	0.19500	0.19540
#0899 - 17	23.20560	11.60270	11.60290	2.25340	1.12990	1.12350	0.68720	0.68730	0.19470	0.19520
#0899 - 18	23.20590	11.60310	11.60280	2.25340	1.12970	1.12370	0.68660	0.68710	0.19470	0.19440
#0899 - 19	23.20550	11.60270	11.60280	2.25350	1.12980	1.12380	0.68680	0.68690	0.19390	0.19420
#0899 - 20	23.20510	11.60240	11.60270	2.25370	1.13000	1.12380	0.68660	0.68660	0.19400	0.19400
#0899 - 21	23.20550	11.60280	11.60270	2.25350	1.13120	1.12230	0.68680	0.68660	0.19400	0.19470
#0899 - 22	23.20520	11.60250	11.60260	2.25320	1.12970	1.12340	0.68690	0.68710	0.19430	0.19450

Note: Boxed data indicate a transposition of the laminate about the y-axis.  
 Shaded data indicate values out of specification.




**Figure 7. Illustration of the Defined Laminate Dimensions for Tables 1, 2, 3, and 4.**

The converse also holds true. Once a  $180^\circ$  transposition about the Y-axis of a laminate has occurred, forcing a rivet through these centrally located rivet holes will cause an offset of the entire laminate. Therefore, the assembly is forced to buckle when the bushings are placed through the ends of the laminate stack. Figure 8 visually depicts the transposition and buckling scenario.

Further evidence of this scenario is suggested by the displacement/buckling location within the laminate stack as reported previously. The displacement and buckling location matches precisely with the boxed data laminate numbers in Table 1. In strap pack 1548, the first laminate is visibly displaced (refer to Figure 5), and for strap pack 0899, the third and eleventh laminates are displaced (refer to Figure 4).





**Figure 8. Illustration of the Transposition About the Y-Axis and Buckling Scenario.**

Based upon these initial findings of the QDR exhibits, ARL-WMRD was asked to perform a full dimensional analysis of three randomly selected laminates from each of the nine individual laminate sets received, in addition to two single separate laminates. Tables 2–4 list the data acquired using the CMM.

The only significant finding in the data in Table 2 was that the first extra laminate inspected was considerably out of tolerance with respect to its width dimensions. The transposition event is not discernable within this data due to the absence of the data from the complete sets. Three laminates are not enough to establish a pattern in the measurement data.

Based upon the findings in Table 3, it was obvious that a complete laminate set must be dimensionally checked for the transposition about the Y-axis to be seen within a laminate set.

**Table 2. Dimensional Data for Randomly Selected Individual Laminate Sets and Odd Laminates**

Laminate Specification Tolerance	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F	DIM. G	DIM. H	DIM. I	DIM. J	DIM. K	DIM. L	DIM. M	DIM. N
1172 - 7	23.2009	11.6004	11.6004	2.2527	1.1261	1.1266	1.1042	0.6635	1.5568	1.5572	1.5569	0.7922	0.7924	24.8555
1172 - 16	23.2007	11.6003	11.6003	2.2522	1.1263	1.1259	1.1029	0.6622	1.5567	1.5579	1.5582	0.7932	0.7922	24.8534
1172 - 21	23.2005	11.6002	11.6002	2.2523	1.1262	1.1260	1.1031	0.6637	1.5570	1.5570	1.5571	0.7922	0.7922	24.8491
1173 - 2	23.2005	11.6002	11.6002	2.2526	1.1259	1.1267	1.1033	0.6641	1.5539	1.5549	1.5550	0.7906	0.7906	24.8482
1173 - 9	23.1982	11.5991	11.5991	2.2533	1.1282	1.1251	1.1028	0.6649	1.5533	1.5561	1.5562	0.7921	0.7921	24.8497
1173 - 19	23.2007	11.6003	11.6003	2.2534	1.1267	1.1267	1.1028	0.6635	1.5535	1.5573	1.5572	0.7927	0.7927	24.8541
1167 - 1	23.2007	11.6003	11.6003	2.2511	1.1259	1.1252	1.1026	0.6640	1.5539	1.5556	1.5545	0.7927	0.7910	24.8569
1167 - 8	23.2004	11.6002	11.6002	2.2511	1.1261	1.1250	1.1037	0.6634	1.5541	1.5566	1.5555	0.7910	0.7914	24.8521
1167 - 20	23.2002	11.6001	11.6001	2.2510	1.1265	1.1246	1.1030	0.6637	1.5545	1.5570	1.5572	0.7914	0.7925	24.8546
1169 - 2	23.2008	11.6004	11.6004	2.2519	1.1266	1.1253	1.1040	0.6636	1.5537	1.5555	1.5555	0.7921	0.7921	24.8569
1169 - 13	23.2006	11.6003	11.6003	2.2523	1.1269	1.1254	1.1020	0.6650	1.5556	1.5566	1.5578	0.7939	0.7939	24.8505
1169 - 22	23.2007	11.6003	11.6003	2.2518	1.1275	1.1243	1.1021	0.6644	1.5552	1.5576	1.5581	0.7947	0.7947	24.8549
1168 - 2	23.2009	11.6004	11.6004	2.2515	1.1261	1.1266	1.1036	0.6656	1.5512	1.5567	1.5561	0.7915	0.7915	24.8536
1168 - 12	23.2009	11.6004	11.6004	2.2514	1.1264	1.1250	1.1038	0.6645	1.5533	1.5566	1.5569	0.7921	0.7921	24.8569
1168 - 20	23.2004	11.6002	11.6002	2.2520	1.1265	1.1255	1.1029	0.6642	1.5541	1.5571	1.5577	0.7922	0.7922	24.8582
1174 - 4	23.2015	11.6007	11.6007	2.2515	1.1250	1.1266	1.1034	0.6651	1.5548	1.5565	1.5566	0.7933	0.7933	24.8586
1174 - 11	23.2011	11.6005	11.6005	2.2502	1.1246	1.1256	1.1057	0.6657	1.5553	1.5561	1.5571	0.7929	0.7929	24.8510
1174 - 20	23.2017	11.6008	11.6008	2.2507	1.1248	1.1260	1.1052	0.6644	1.5560	1.5571	1.5569	0.7928	0.7928	24.8547
1175 - 1	23.2009	11.6004	11.6004	2.2508	1.1248	1.1260	1.1050	0.6644	1.5546	1.5559	1.5554	0.7919	0.7919	24.8505
1175 - 12	23.2021	11.6010	11.6010	2.2512	1.1247	1.1266	1.1047	0.6653	1.5546	1.5575	1.5569	0.7930	0.7930	24.8525
1175 - 19	23.2018	11.6009	11.6009	2.2503	1.1241	1.1263	1.1040	0.6644	1.5548	1.5568	1.5576	0.7923	0.7923	24.8563
1176 - 3	23.2009	11.6004	11.6004	2.2519	1.1273	1.1246	1.1041	0.6640	1.5568	1.5570	1.5572	0.7934	0.7934	24.8569
1176 - 10	23.2004	11.6002	11.6002	2.2520	1.1269	1.1251	1.1037	0.6630	1.5570	1.5570	1.5567	0.7934	0.7934	24.8545
1176 - 21	23.2005	11.6002	11.6002	2.2515	1.1270	1.1245	1.1040	0.6633	1.5555	1.5552	1.5557	0.7911	0.7911	24.8534
1177 - 5	23.2007	11.6003	11.6003	2.2517	1.1252	1.1265	1.1043	0.6640	1.5565	1.5566	1.5567	0.7913	0.7913	24.8526
1177 - 11	23.2003	11.6001	11.6001	2.2512	1.1263	1.1249	1.1044	0.6646	1.5574	1.5551	1.5566	0.7916	0.7926	24.8483
1177 - 17	23.2003	11.6001	11.6001	2.2505	1.1265	1.1240	1.1060	0.6656	1.5569	1.5561	1.5561	0.7928	0.7912	24.8476
Extra #1	23.2060	11.6030	11.6030	2.2510	1.1223	1.1287	1.1090	0.6641	1.6145	1.6125	1.6132	0.8495	0.8525	24.9166
Extra #2	23.2058	11.6029	11.6029	2.2512	1.1281	1.1231	1.1072	0.6631	1.5629	1.5599	1.5578	0.7980	0.7964	24.8574

Note: Shaded data indicate a value out of specification.

**Table 3. Dimensional Data for the Holes and Radii of Randomly Selected Laminates**

Laminate	Hole 1	Hole 2	Hole 3	Hole 4	Rad. 3	Rad. 4	Rad. 5	Rad. 6	Rad. 7	Rad. 8	Rad. 9	Rad. 10	Rad. 11	Rad. 12
Specification	0.6883	0.6883	0.1955	0.1955	0.82	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	0.82
Tolerance	+0.0002 -0.0003	+0.0002 -0.0003	±0.0005	±0.0005	±0.03	±0.03	±0.03	±0.03	±0.03	±0.03	±0.03	±0.03	±0.03	±0.03
1172 - 7	0.6876	0.6871	0.1941	0.1940	0.8270	1.9290	1.9626	2.0030	1.9692	1.8446	1.8539	1.9981	1.9854	0.8276
1172 - 16	0.6868	0.6866	0.1944	0.1942	0.8244	2.0484	1.8565	1.9534	1.9709	1.9519	1.9043	1.9029	1.9606	0.8283
1172 - 21	0.6872	0.6868	0.1938	0.1944	0.8247	2.0259	1.8329	1.8933	1.9754	1.8884	1.9040	1.8360	2.0176	0.8239
1173 - 2	0.6874	0.6869	0.1972	0.1941	0.8226	1.9733	1.7778	2.0883	1.9952	2.0374	1.9157	1.9600	2.0074	0.8251
1173 - 9	0.6829	0.6871	0.1937	0.1941	0.8258	1.9425	1.8803	1.9941	1.9497	1.9171	1.9541	1.9042	1.9354	0.8257
1173 - 19	0.6874	0.6866	0.1942	0.1942	0.8254	2.0131	2.1237	1.9602	1.9923	1.9126	1.8791	1.8790	2.0036	0.8253
1167 - 1	0.6873	0.6872	0.1942	0.1942	0.8291	2.0871	2.0342	1.9137	1.9892	2.1128	1.9768	2.0107	1.9742	0.8270
1167 - 8	0.6877	0.6875	0.1940	0.1943	0.8250	1.9683	2.0187	1.9850	2.0251	2.0125	1.9752	1.9662	2.0049	0.8267
1167 - 20	0.6878	0.6877	0.1947	0.1949	0.8269	1.8214	1.8887	1.9344	2.0394	2.0157	2.0227	1.9634	1.9666	0.8275
1169 - 2	0.6874	0.6869	0.1930	0.1941	0.8298	1.9752	1.9645	1.9998	1.9574	2.0285	1.8977	2.0209	1.9634	0.8263
1169 - 13	0.6868	0.6865	0.1928	0.1939	0.8243	2.0019	1.8545	1.9458	1.9964	1.8848	1.8622	1.9823	1.9772	0.8256
1169 - 22	0.6876	0.6873	0.1973	0.1932	0.8293	1.9515	1.9164	1.9305	1.9391	1.8502	1.8860	1.9524	1.9291	0.8249
1168 - 2	0.6876	0.6869	0.1947	0.1944	0.8262	1.9409	1.8675	1.9612	2.0046	1.9869	1.9440	1.9150	1.9976	0.8265
1168 - 12	0.6872	0.6878	0.1943	0.1941	0.8264	2.0093	1.8277	1.9816	1.9938	1.9698	1.9213	1.9549	1.9989	0.8296
1168 - 20	0.6877	0.6868	0.1942	0.1941	0.8306	1.9896	1.9602	1.9614	2.0111	1.9938	1.9131	1.8419	1.9830	0.8272
1174 - 4	0.6871	0.6873	0.1945	0.1939	0.8308	1.9845	1.9764	1.9378	1.9965	1.9691	1.8404	1.8854	1.9940	0.8263
1174 - 11	0.6878	0.6874	0.1946	0.1945	0.8262	2.0329	1.8427	1.9972	1.9932	1.9673	1.9593	1.9449	1.9822	0.8237
1174 - 20	0.6873	0.6870	0.1935	0.1941	0.8270	1.9331	1.8613	1.9042	1.9365	2.0350	1.8910	1.9486	1.9658	0.8260
1175 - 1	0.6863	0.6875	0.1948	0.1947	0.8257	1.8775	1.9290	1.9699	1.9482	2.0053	1.9175	1.9006	1.9907	0.8239
1175 - 12	0.6871	0.6873	0.1941	0.1944	0.8235	2.0131	1.8561	1.8926	1.9780	2.0203	1.9513	1.9262	1.9812	0.8269
1175 - 19	0.6870	0.6871	0.1943	0.1936	0.8260	1.9734	1.8671	2.0540	1.9908	1.9741	1.8698	2.0340	2.0055	0.8285
1176 - 3	0.6882	0.6881	0.1948	0.1947	0.8277	1.9827	2.0540	1.8037	2.0052	1.9236	1.9234	2.0219	2.0085	0.8283
1176 - 10	0.6871	0.6871	0.1925	0.1936	0.805	2.0038	2.0969	1.9254	2.0123	1.9922	1.8580	1.8446	2.0432	0.8236
1176 - 21	0.6873	0.6865	0.1932	0.1935	0.8243	2.0758	1.6509	1.9837	1.9400	1.9477	1.9817	1.9098	1.9746	0.8286
1177 - 5	0.6876	0.6863	0.1935	0.1937	0.8250	1.9244	2.0392	1.9729	1.9815	1.9178	1.9123	1.8865	1.9592	0.8269
1177 - 11	0.6871	0.6876	0.1941	0.1942	0.8231	1.9437	1.9414	1.9728	2.0209	1.9946	1.9038	1.9012	1.9868	0.8249
1177 - 17	0.6872	0.6867	0.1939	0.1919	0.8240	1.9174	1.9714	1.9568	1.9662	1.9304	1.8684	1.9497	2.0015	0.8233
Extra #1	0.6849	0.6864	0.1934	0.1939	0.8235	1.9737	1.9599	2.0032	1.8058	1.9664	1.9715	1.9674	1.9464	0.8571
Extra #2	0.6872	0.6867	0.1931	0.1935	0.8242	1.9839	2.0143	1.9860	1.9847	1.9881	1.9779	1.9673	1.9788	0.8274

Note: Shaded data indicates a value out of specification.

**Table 4. Dimensional Examination of Laminate Set 1174**

Laminate Specification Tolerance	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F	DIM. G	DIM. H	DIM. I	DIM. J	DIM. K	DIM. L	DIM. M	DIM. N		
	23.200 ± 0.010	11.600 ± 0.010	11.600 ± 0.010	2.250 ± 0.010	1.125 ± 0.010	1.125 ± 0.010	1.100 ± 0.010	0.660 ± 0.010	1.550 ± 0.010	1.550 ± 0.010	1.550 ± 0.010	0.790 ± 0.010	0.790 ± 0.010	24.840 REF.		
1174-1	23.2001	11.6005	11.6005	2.2513	1.1249	1.1263	1.1053	0.6635	1.5544	1.5564	1.5560	0.7903	0.7912	24.8483		
1174-2	23.2014	11.6007	11.6007	2.2508	1.1246	1.1262	1.1061	0.6653	1.5532	1.5555	1.5543	0.7907	0.7922	24.8500		
1174-3	23.2011	11.6005	11.6005	2.2508	1.1245	1.1264	1.1058	0.6608	1.5567	1.5572	1.5561	0.7909	0.7908	24.8561		
1174-4	23.2018	11.6009	11.6009	2.2517	1.1254	1.1266	1.1063	0.6657	1.5549	1.5559	1.5564	0.7902	0.8221	24.8568		
1174-5	23.2017	11.6008	11.6008	2.2511	1.1248	1.1263	1.1057	0.6635	1.5557	1.5573	1.5574	0.7912	0.7914	24.8519		
1174-6	23.2012	11.6006	11.6006	2.2513	1.1249	1.1263	1.1052	0.6641	1.5554	1.5554	1.5563	0.7902	0.7904	24.8512		
1174-7	23.2015	11.6007	11.6007	2.2507	1.1247	1.1261	1.1059	0.6662	1.5549	1.5571	1.5553	0.7901	0.7883	24.8440		
1174-8	23.2016	11.6008	11.6008	2.2512	1.1254	1.1257	1.1054	0.6643	1.5563	1.5509	1.5572	0.7901	0.7905	24.8481		
1174-9	23.2013	11.6006	11.6006	2.2511	1.1253	1.1257	1.1050	0.6646	1.5558	1.5566	1.5576	0.7908	0.7914	24.8559		
1174-10	23.2014	11.6007	11.6007	2.2509	1.1251	1.1258	1.1042	0.6636	1.5567	1.5578	1.5583	0.7907	0.7905	24.8534		
1174-11	23.2009	11.6004	11.6004	2.2504	1.1248	1.1256	1.1055	0.6655	1.5559	1.5563	1.5575	0.7897	0.7923	24.8440		
1174-12	23.2017	11.6008	11.6008	2.2516	1.1264	1.1252	1.1046	0.6646	1.5564	1.5578	1.5577	0.7925	0.7893	24.8561		
1174-13	23.2011	11.6005	11.6005	2.2509	1.1259	1.1250	1.1057	0.6649	1.5559	1.5578	1.5563	0.7913	0.7908	24.8486		
1174-14	23.2011	11.6005	11.6005	2.2510	1.1260	1.1250	1.1050	0.6637	1.5568	1.5547	1.5577	0.7915	0.7924	24.8507		
1174-15	23.2011	11.6005	11.6005	2.2514	1.1262	1.1253	1.1048	0.6643	1.5569	1.5582	1.5580	0.7910	0.7947	24.8589		
1174-16	23.1966	11.5893	11.5893	2.2506	1.1270	1.1240	1.1038	0.6643	1.5567	1.5575	1.5582	0.7923	0.7917	24.8457		
1174-17	23.2008	11.6004	11.6004	2.2505	1.1247	1.1258	1.1052	0.6649	1.5569	1.5576	1.5570	0.7903	0.7923	24.8544		
1174-18	23.2002	11.6001	11.6001	2.2513	1.1249	1.1263	1.1053	0.6648	1.5557	1.5569	1.5569	0.7913	0.7915	24.8524		
1174-19	23.2008	11.6004	11.6004	2.2510	1.1256	1.1254	1.1042	0.6635	1.5566	1.5580	1.5569	0.7920	0.7928	24.8462		
1174-20	23.2009	11.6004	11.6004	2.2507	1.1248	1.1259	1.1034	0.6641	1.5565	1.5579	1.5582	0.7915	0.7921	24.8413		
1174-21	23.2023	11.6011	11.6011	2.2507	1.1252	1.1255	1.1044	0.6639	1.5561	1.5576	1.5568	0.7929	0.7936	24.8536		
1174-22	23.2008	11.6004	11.6004	2.2507	1.1248	1.1258	1.1041	0.6652	1.5567	1.5578	1.5563	0.7916	0.7921	24.8494		
Laminate Specification Tolerance	Hole 1 0.6883 + 0.0002 - 0.0003	Hole 2 0.6883 + 0.0002 - 0.0003	Hole 3 0.1955 • 0.0005	Hole 4 0.1955 • 0.0005	Rad. 1 0.33 • 0.03	Rad. 2 0.33 • 0.03	Rad. 3 0.82 • 0.03	Rad. 4 2.00 • 0.03	Rad. 5 2.00 • 0.03	Rad. 6 2.00 • 0.03	Rad. 7 2.00 • 0.03	Rad. 8 2.00 • 0.03	Rad. 9 2.00 • 0.03	Rad. 10 2.00 • 0.03	Rad. 11 2.00 • 0.03	Rad. 12 0.82 • 0.03
1174-1	0.6871	0.6869	0.1938	0.1942	0.3289	0.3305	0.8226	1.9778	1.9676	1.9245	1.9559	1.8808	1.9280	1.8864	2.0028	0.8248
1174-2	0.6877	0.6877	0.1946	0.1950	0.3296	0.3307	0.8248	1.9669	1.8944	1.9274	1.9603	1.9696	1.9233	1.9246	1.9775	0.8237
1174-4	0.6873	0.6876	0.1946	0.1950	0.3295	0.3307	0.8255	1.9651	1.9481	1.8962	2.0025	1.9648	1.9504	1.7209	1.9754	0.8295
1174-5	0.6871	0.6868	0.1938	0.1935	0.3292	0.3287	0.8239	1.9844	1.7876	1.9239	1.8002	1.9697	1.9076	1.8746	1.9638	0.8263
1174-6	0.6865	0.6872	0.1953	0.1946	0.3310	0.3298	0.8226	2.0348	1.8665	1.8988	1.9731	1.8771	1.8987	2.0432	2.0006	0.8374
1174-7	0.6875	0.6876	0.1941	0.1946	0.3295	0.3295	0.8199	1.9737	1.9834	2.0130	1.9894	1.9914	1.8843	1.8596	2.0018	0.8226

Note: Shaded data indicates values out of specification.



**Table 4. Dimensional Examination of Laminate Set 1174 (continued)**

Laminate	Hole 1	Hole 2	Hole 3	Hole 4	Rad. 1	Rad. 2	Rad. 3	Rad. 4	Rad. 5	Rad. 6	Rad. 7	Rad. 8	Rad. 9	Rad. 10	Rad. 11	Rad. 12
Specification	0.6883	0.6883	0.1955	0.1955	0.33	0.33	0.82	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	0.82
Tolerance	+0.0002 -0.0003	+0.0002 -0.0003	+0.0005 -0.0005	+0.0005 -0.0005	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03	+0.03 -0.03
1174-8	0.6870	0.6871	0.1939	0.1941	0.3283	0.3293	0.8224	1.9471	1.9777	1.9019	1.8591	1.9482	1.8789	1.8724	1.9687	0.8241
1174-9	0.6869	0.6869	0.1942	0.1940	0.3329	0.3287	0.8268	1.9584	2.0757	1.9858	1.9781	1.8931	1.8644	1.9371	2.0004	0.8278
1174-10	0.6865	0.6871	0.1935	0.1938	0.3297	0.3295	0.8259	1.9833	1.9761	1.8952	1.9761	1.9626	1.9568	1.8917	2.0209	0.8262
1174-11	0.6876	0.6877	0.1947	0.1941	0.3292	0.3295	0.8240	2.0396	1.8954	1.9821	1.9799	1.9881	1.9061	1.9543	1.4613	0.8191
1174-12	0.6872	0.6871	0.1945	0.1943	0.3298	0.3257	0.8272	1.9296	1.9014	1.7965	1.9882	1.9612	1.9818	1.9082	2.0327	0.8283
1174-13	0.6883	0.6879	0.1948	0.1954	0.3289	0.3307	0.8239	1.9127	2.0271	1.9636	1.9630	1.9633	1.9113	1.8245	2.0155	0.8236
1174-14	0.6869	0.6867	0.1937	0.1936	0.3287	0.3287	0.8228	2.0057	1.8107	1.8897	1.9843	1.9420	1.9199	1.8668	1.9617	0.8268
1174-15	0.6869	0.6870	0.1938	0.1934	0.3287	0.3287	0.8325	1.9796	1.8559	1.9554	1.9573	1.9906	2.0639	1.9814	1.9854	0.8253
1174-16	0.6826	0.6872	0.1938	0.1941	0.3298	0.3289	0.8211	2.0155	1.9128	1.9569	1.9984	1.9399	1.9248	1.9328	1.9814	0.8280
1174-17	0.6872	0.6875	0.1945	0.1941	0.3290	0.3292	0.8273	1.9687	2.0025	1.8415	2.0244	1.8908	1.9124	1.9128	1.8539	0.8262
1174-18	0.6883	0.6872	0.1948	0.1952	0.3296	0.3204	0.8263	1.9597	1.9260	1.9520	1.9455	1.9574	1.9639	1.9621	2.0013	0.8259
1174-19	0.6873	0.6872	0.1939	0.1940	0.3292	0.3221	0.8266	1.9341	1.9488	1.9399	1.9524	1.9600	1.9864	1.9404	1.9963	0.8227
1174-20	0.6867	0.6869	0.1939	0.1941	0.3298	0.3310	0.8176	2.0006	1.9381	1.9526	1.9688	1.9945	1.8490	1.9313	1.9854	0.8228
1174-21	0.6873	0.6871	0.1942	0.1943	0.3296	0.3257	0.8236	1.9386	1.9032	1.9882	1.9148	1.9211	2.0349	1.9759	2.0193	0.8243
1174-22	0.6872	0.6869	0.1942	0.1942	0.3304	0.3309	0.8269	1.9479	1.7793	1.8999	1.9991	1.9857	1.9446	1.8488	2.0402	0.8257

Note: Shaded data indicates values out of specification.

Therefore, one complete laminate set (SN 003343-1174, laminates 1–22) was dimensionally checked for conformance to the governing drawings. The results are listed in Table 4. Also, it was acutely apparent from the randomly selected laminates that a problem existed with the hole dimensions. The radii also appeared to be out of specification; however, the edge finishing of the laminates might be effecting these results as previously discussed. Regardless, the hole dimensions are much more critical from a stress analysis standpoint than the radii dimensions.

A 180° transposition about the Y-axis was not seen for any laminate within this laminate assembly set. It cannot be inferred from this investigation that the transposition of the laminates is either an abundant or infrequent occurrence. ARL-WMRD looked at only one complete laminate set, other than the QDR exhibits. A proper estimation of the frequency of this occurrence should be drawn from a larger population of laminate sets. However, the frequency with which the hole dimensions are out of specification (smaller than the acceptable value) is significant and distressing. Considering the hole diameters were found to be smaller than the acceptable values, the bushings and rivets must have been forced through these holes during assembly. The bushings and rivets are governed by specifications BP-7-211421028 and NAS-529, respectively [9, 10]. Forcing the rivets through small holes would place undo stresses on the edges of the hole as well as the bushings and rivets. If the bushings and rivets must be forced in place, it could contribute to the buckling condition based on the assumption that the hole tolerances were probably set to allow for imperfections in part symmetry. If the holes are too small, individual laminates are forced to positions that may or may not align with the other laminates. This concept is depicted in Figure 8. In addition, creating stress concentrations on the inner diameters of these holes as well as the bushings and rivets might lead to serious problems for parts under fatigue loading conditions.


The laminates were also checked for conformance with EPB-4-321. No discrepancies or nonconformances with the specification were found. The surface finishes were all within 2–4 Ra, which was well within the specified 8 Ra. Appendices A–D present the data acquired on the edge finishing for the individual laminates of the sets analyzed. Strap packs 0899 and 1548, were examined, in addition to the three randomly selected laminates from each laminate set, the

two extra laminates, and the one complete laminate set 1174. The data were acquired from an image analysis system equipped with a CCD camera. The values obtained are based on a calibration performed on the laminates and are accurate only to one decimal place. The interior hole edge finishing data could not be acquired due to the small size of the holes. A boroscope small enough to acquire this data was not available. However, the edge finishes of all holes on all laminates were visually examined using optical microscopy techniques at 10×–65× magnification. Although no measurements could be taken, ARL-MD verified that all hole edges appeared properly broken and no discrepancies were observed.

## 5. Metallography

A representative longitudinal and transverse section of the strap pack laminates from 0899 and 1548 were mounted and metallographically prepared. The specimens were mounted in Bakelite with edge retention and rough-polished with 180–600-grit silicon carbide paper. Fine-polishing was accomplished with hand-polishing wheels using 3- $\mu$ m and 1- $\mu$ m diamond suspensions. Final polishing was performed with a vibratory unit and 0.06- $\mu$ m colloidal silica. The as-polished specimens exhibited no significant inclusions per ASTM-E-45 [11].

The polished specimens were subsequently etched with Vilella's Reagent to reveal the resultant microstructure. The longitudinal and transverse sections of this semiaustenitic stainless steel exhibited fine carbides uniformly distributed within a tempered martensitic structure as shown in Figures 9–12, respectively, for strap packs 1548 and 0899. The detrimental delta (free ferrite) phase was not apparent to any discernable degree. This structure is consistent with the prior heat treatment, cold rolling, and tempering schedule of the AM-355 precipitation hardenable stainless steel. The material conformed to the governing specification HMS 6-1073.



**Figure 9. Micrograph of a Longitudinal Section of 1548. Vilella's Etch. Mag. 500 $\times$ .**



**Figure 10. Micrograph of a Longitudinal Section of 0899. Vilella's Etch. Mag. 500 $\times$ .**





**Figure 11. Micrograph of a Transverse Section of 1548. Vilella's Etch. Mag. 500x.**



**Figure 12. Micrograph of a Transverse Section of 0899. Vilella's Etch. Mag. 500x.**

## 6. Conclusions

The examination revealed that, for the two assembly QDR exhibits, the buckling along the length was caused by a combination of controlling factors. The first being a dimensional nonconformity with respect to the hole diameters, and the second being a transposition about the Y-axis of the part that is not perfectly symmetric. All assembly laminates examined were found to have hole diameters smaller than allowed per the specified part drawing BP-7-211421023. The unassembled laminate sets were also examined and were found to contain the same dimensional nonconformity. The transposition of the respective positions of the laminates within the pack is prohibited after hole boring or reaming, per EPB-4-321, para. 3.3.1.3.1 [4]. However, considering the laminates may have the finishing operations performed individually or in subsets of the pack, a Y-axis transposition of a laminate with respect to its rotational orientation is most likely the root-cause of the buckling, since it is not distinctly prohibited per the specification (refer to the discussion section). All other characteristics of the laminates and assemblies were found to conform to the governing part drawings and specifications.

## 7. References


1. Lockheed Support Systems, Inc. "Quality Deficiency Report for Exhibit Part Number 7-211421035-5 and Serial Number 003343-0899." W81CL8940027, Fort Hood Army Airfield, Fort Hood, TX, 8 March 1994.
2. Lockheed Support Systems, Inc. "Quality Deficiency Report for Exhibit Part Number 7-211421035-5 and Serial Number 003343-1548." W81CL8940085, Fort Hood Army Airfield, Fort Hood, TX, 16 November 1994.
3. McDonnell Douglas Helicopter Company. "Strap Assembly - Tail Rotor." Drawing Package BP-7-211421035, 5000 East McDowell Road Mesa, AZ, 4 April 1991.
4. McDonnell Douglas Helicopter Company. "Finishing Holes, Edges, and Surfaces of AH-64 Main and Tail Rotor Blade Retention Laminates." Engineering Process Bulletin 4-321 (EPB-4-321), Revision E, 5000 East McDowell Road, Mesa, AZ, 3 June 1994.
5. McDonnell Douglas Helicopter Company. "Strap Assembly - Tail Rotor." Drawing Package BP-7-211421035, 5000 East McDowell Road Mesa, AZ, 4 April 1991.
6. McDonnell Douglas Helicopter Company. "Steel, Sheet and Strip, Corrosion Resistant, AM-355 CRT (Cold Rolled and Tempered)." Material Specification HMS-6-1073 Rev. E., 5000 East McDowell Road, Mesa, AZ, 9 January 1990.
7. McDonnell Douglas Helicopter Company. "Identification of Detail Parts and Assemblies." Process Specification HP 8-5 Rev. T, 5000 East McDowell Road, Mesa, AZ, 8 September 1993.
8. McDonnell Douglas Helicopter Company. "Serialization of Parts and Subassemblies, and Numbering for Material Control." Process Specification HP 8-8 Rev. E, 5000 East McDowell Road, Mesa, AZ, 29 November 1993.
9. McDonnell Douglas Helicopter Company. "Bushing, Tension-Torsion Strap, Tail Rotor." Drawing Package BP-7-211421028, 5000 East McDowell Road, Mesa, AZ, 2 October 1989.
10. National Aerospace Standards Committee, Aerospace Industry Association of America Inc. "Rivet-Flat Head, Hi-Shear, Close Tolerance Shank." National Aerospace Standard NAS-529, 1725 De Sales Street., NW, Washington, DC, 15 February 1983.
11. American Society for Testing and Materials, Standard Test Method ASTM-E-45. "Determining the Inclusion Content of Steel." 100 Barr Harbor Drive, West Conshohocken, PA, 1995.

INTENTIONALLY LEFT BLANK.

**Appendix A:**  
**Edge Break Data for Strap Pack 0899**

INTENTIONALLY LEFT BLANK.

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. F
THICKNESS 0.01385		QUAL. ENG. N. PANDA		
S/N 0899-1		REVISED BY J REDMAN 09/06/86		
		02/05/95		




I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.607	8.982							11.085	10.224
L - TOP							2.872	3.195							1.482	1.864
P - BOTTOM							1.362	2.224							1.374	1.929

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01381		QUAL. ENG. N. PANDA	09/06/86	
S/N 0899-2		REVISED BY J. REDMAN	02/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.899	8.780							10.256	9.802
L - TOP							2.704	3.106							1.901	1.700
P - BOTTOM							1.973	2.038							1.901	2.116

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01360		QUAL. ENG. N. PANDA	09/06/86	
S/N 0899-3		REVISED BY J REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.665	8.501							9.733	10.339
L - TOP							2.654	3.062							2.202	1.954
P - BOTTOM							1.929	2.441							1.864	1.581

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01365		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-4		REVISED BY J REDMAN 09/05/95		



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.145	8.501							10.398	9.356
L - TOP							2.496	3.008							1.887	1.616
P - BOTTOM							1.995	2.183							1.837	1.983

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01381 S/N 0899-5		DUAL. ENG. N. PANDA REVISED BY J. REDMAN 09/06/86 09/05/95		

I	LAMINATE THICKNESS	.014 + -.0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.781	9.242							9.732	9.627
L - TOP							2.659	2.376							2.441	2.355
P - BOTTOM							2.332	2.062							2.076	2.038

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS <u>0.01375</u> S/N <u>0899-6</u>		QUAL. ENG. N. PANDA REVISED BY J REDMAN 02/05/95 09/06/86		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.310	8.602							9.489	9.867
L - TOP							2.485	3.316							2.179	1.929
P - BOTTOM							1.901	2.116							2.320	2.183

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01370		DUAL. ENG. N. PANDA	09/06/86	
S/N 0899-7		REVISED BY J. REDMAN	02/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.710	8.147							9.331	9.585
L - TOP							2.878	4.294							2.598	2.224
P - BOTTOM							2.062	1.537							1.833	2.183

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS <u>0.01380</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>0899-8</u>		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS .014+- .0007															
II	FLATNESS REQD .008 MIN															
III, IV	EDGEBREAK REQD .001 MIN															

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.447	8.681							0.437	9.637
L - TOP							3.154	3.222							2.008	2.359
P - BOTTOM							2.161	2.345							1.565	2.032

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01366		DUAL. ENG. N. PANDA 09/06/86		
S/N 0899-9		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS .014+- .0007															
II	FLATNESS REQD .008 MIN															
III, IV	EDGEBREAK REQD .001 MIN															


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.314	9.301							9.610	9.544
L - TOP							2.345	2.147							2.329	2.291
P - BOTTOM							1.874	2.252							2.237	2.237

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS <u>0.01386</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>0899-10</u>		REVISED BY J. REDMAN	02/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS RECD	.008 MIN
III, IV	EDGEBREAK RECD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.344	9.207							0.299	10.199
L - TOP							3.612	3.146							1.901	1.986
P - BOTTOM							1.618	1.828							2.198	2.030

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01376		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-11		REVISED BY J REDMAN 02/05/95		


I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.204	10.519							11.163	10.365
L - TOP							1.995	1.754							1.515	2.062
P - BOTTOM							1.645	2.224							1.267	1.794

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01370		QUAL. ENG. N. PANDA		
S/N 0899-12		REVISED BY J REDMAN 09/06/86		
		02/05/95		



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.702	10.772							10.636	10.347
L - TOP							2.415	1.618							2.003	1.621
P - BOTTOM							2.446	1.712							1.197	1.873

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01370</b> S/N <b>0899-13</b>		DUAL. ENG. REVISED BY	N. PANDA J REDMAN	09/06/86 02/05/95


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							11.024	10.569							11.099	10.753
L - TOP							1.458	1.715							1.569	1.517
P - BOTTOM							1.321	1.343							1.321	1.269

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01386</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>0899-14</u>		REVISED BY J REDMAN	09/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							11.084	10.508							10.674	11.077
L - TOP							1.671	1.809							2.146	1.757
P - BOTTOM							1.372	1.635							1.860	1.125

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00986	REV.NO. E
THICKNESS <u>0.01385</u>		DUAL. ENG. REVISED BY	N. PANDA J. REDMAN	09/06/86 02/05/95
S/N <u>0899-15</u>				

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.969	11.218							10.589	1.032
L - TOP							.992	1.419							.739	.723
P - BOTTOM							2.240	1.269							.569	.424

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00986	REV. NO. E
THICKNESS 0.01377		DUAL. ENG. N. PANDA	09/06/86	
S/N 0899-16		REVISED BY J. REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							0.808	10.787								11.708 11.408
L - TOP							.638	1.714								.168 .516
P - BOTTOM							.800	1.416								.228 .118

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01371		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-17		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.234	9.031							1.353	1.058
L - TOP							1.964	2.628							1.405	1.823
P - BOTTOM							1.407	2.250							1.125	1.197

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01374		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-18		REVISED BY J REDMAN 09/05/95		

1	LAMINATE THICKNESS .014 + -.0007														
11	FLATNESS REQD .008 MIN														
111, 1V	EDGEBREAK REQD .001 MIN														


POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.375	9.710								10.211	10.528
L - TOP							2.145	2.763								2.083	.954
P - BOTTOM							.725	1.618								.863	.496

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01376</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>0899-19</u>		REVISED BY J. REDMAN	02/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.486	10.901							0.445	0.269
L - TOP							1.618	1.809							2.083	1.952
P - BOTTOM							1.779	1.745							1.700	2.068

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01385 S/N 0899-20		QUAL. ENG. N. PANDA	REVISED BY J. REDMAN	09/06/86 02/05/95

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.406	8.970								10.393
L - TOP							1.888	3.266								2.453
P - BOTTOM							1.766	1.896								2.170

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01385		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-21		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.744	9.943								9.752 11.312
L - TOP							2.843	2.295								2.173 1.449
P - BOTTOM							1.700	1.682								2.007 1.399

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 0086	REV. NO. E
THICKNESS 0.01365		QUAL. ENG. N. PANDA 09/06/86		
S/N 0899-22		REVISED BY J REDMAN 09/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.948	9.464							9.705	10.911
L - TOP							2.83	2.869							2.237	2.038
P - BOTTOM							1.902	1.792							2.008	1.242

NOTE: NOT TO SCALE

**Appendix B:**  
**Edge Break Data for Strap Pack 1548**

INTENTIONALLY LEFT BLANK.

SUPP NO.	PART NAME	PART NO.	OPERATION #20 of page 6	REV. NO.
Q02	LAMINATE SET-TAIL ROTOR	7-211421023-9		E
THICKNESS 0.01420		DUAL. ENG. N. PANDA 09/06/86		
S/N 1548-1		REVISED BY J REDMAN 09/05/95		

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.846	10.242								12.097	11.841
L - TOP							1.526	1.869								1.097	1.024
P - BOTTOM							1.537	2.412								1.253	1.526


  

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF page 6	REV. NO. E
THICKNESS <u>0.01415</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>1548-2</u>		REVISED BY J. REDMAN	02/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.455	10.444							11.324	12.349
L - TOP							2.106	2.038							1.864	1.095
P - BOTTOM							1.995	1.754							1.308	1.024

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01414</b> S/N <b>1548-3</b>		DUAL. ENG. N. PANDA REVISED BY J. REDMAN 02/05/95 09/06/86		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							11.893	9.553							11.917	11.781
L - TOP							1.864	2.339							1.283	1.779
P - BOTTOM							1.027	2.629							1.283	1.097

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01417</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1548-4</u>		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS .014+- .0007															
II	FLATNESS REQD .008 MIN															
III, IV	EDGEBREAK REQD .001 MIN															

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.726	10.407							1.743	1.658
L - TOP							1.986	2.257							1.416	1.419
P - BOTTOM							1.757	1.794							1.471	1.308

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01416		QUAL. ENG. N. PANDA		
S/N 1548-5		REVISED BY J REDMAN 09/06/86		
		09/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							11.104	11.115							11.237	12.099
L - TOP							1.818	1.986							2.278	1.253
P - BOTTOM							1.405	1.496							1.962	1.145

NOTE: NOT TO SCALE

SUPP NO. QO2	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS <b>0.01415</b> S/N <b>1548-6</b>		DUAL. ENG. N. PANDA	09/06/86	
		REVISED BY J REDMAN	02/05/95	

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.636	11.484							1.196	9.387
L - TOP							2.198	1.814							2.075	2.198
P - BOTTOM							2.656	1.550							1.405	2.355

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. F
THICKNESS 0.01417		DUAL. ENG. N. PANDA	09/06/86	
S/N 1548-7		REVISED BY J. REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							11.187	10.611							10.125	9.901
L - TOP							2.127	2.656							2.092	2.237
P - BOTTOM							1.634	1.561							2.023	2.145

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01416</b> S/N <b>1548-8</b>		QUAL. ENG. N. PANDA 09/06/86 REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.406	10.529								10.215	10.528
L - TOP							1.706	1.987								2.654	2.198
P - BOTTOM							1.845	2.320								1.828	1.618

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01431		QUAL. ENG. N. PANDA 09/06/86		
S/N 1548-9		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.862	9.337								10.950
L - TOP							2.569	2.443								1.828
P - BOTTOM							1.899	2.390								1.687

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01425</u> S/N <u>1548-10</u>		QUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 02/05/95		

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.856	10.105								10.414
L - TOP							2.621	2.355								2.240
P - BOTTOM							1.795	1.704								2.341

I LAMINATE THICKNESS .014+- .0007 II FLATNESS REQD .008 MIN III, IV EDGEBREAK REQD .001 MIN
---

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01415</u> S/N <u>1548-11</u>		QUAL. ENG. N. PANDA REVISED BY J REDMAN 09/06/86 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS RECD	.008 MIN
III, IV	EDGEBREAK RECD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.083	10.898								11.467	11.001
L - TOP							1.692	1.775								1.642	1.863
P - BOTTOM							1.446	1.775								1.424	1.548

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01415</b> S/N <b>1548-12</b>		QUAL. ENG. N. PANDA	09/06/86	
		REVISED BY J. REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.670	11.391								10.439
L - TOP							2.218	1.951								2.426
P - BOTTOM							2.167	1.548								1.372

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of pages 6	REV. NO. E
THICKNESS <u>0.01422</u> S/N <u>1548-13</u>		QUAL. ENG. N. PANDA 09/06/86 REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS RECD	.008 MIN
III, IV	EDGEBREAK RECD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							11.099	10.320								10.888	11.024
L - TOP							1.683	1.971								2.138	1.441
P - BOTTOM							1.817	2.065								1.467	1.890

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS <u>0.01411</u> S/N <u>1548-14</u>		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 02/05/95		



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.873	10.042							11.159	11.719
L - TOP							2.905	2.262							1.665	1.572
P - BOTTOM							1.964	1.764							1.864	1.227

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01411		DUAL. ENG. N. PANDA 09/06/86		
S/N 1548-15		REVISED BY J. REDMAN 02/05/95		


I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							11.231	9.594								10.370	11.435
L - TOP							2.003	2.659								2.594	1.917
P - BOTTOM							1.301	2.635								1.775	1.424

NOTE: NOT TO SCALE


SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS <u>0.01421</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>1548-16</u>		REVISED BY J REDMAN	02/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.063	9.122							10.504	10.561
L - TOP							4.001	3.444							2.112	2.444
P - BOTTOM							1.449	2.000							1.723	1.446

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF page 6	REV. NO. E
THICKNESS 0.01416		DUAL. ENG. N. PANDA	09/06/86	
S/N 1548-17		REVISED BY J. REDMAN	09/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.889	9.550								11.364
L - TOP							1.823	2.198								1.795
P - BOTTOM							1.671	2.766								1.353

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01415</b> S/N <b>1548-18</b>		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.882	9.918								11.350	10.786
L - TOP								2.366	2.023							2.212	1.971
P - BOTTOM								1.516	2.415							1.020	1.642


  

NOTE: NOT TO SCALE





SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of pages 6	REV. NO. E
THICKNESS <u>0.01415</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>1548-20</u>		REVISED BY J REDMAN	02/05/95	




I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.921	10.299								10.367
L - TOP							1.444	2.198								2.138
P - BOTTOM							1.992	1.550								1.833

NOTE NOT TO SCALE


SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01418</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>1548-21---</u>		REVISED BY J. REDMAN	09/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.021	10.175							1.166	1.539
L - TOP							1.723	1.847							1.693	1.248
P - BOTTOM							2.394	1.899							1.343	1.496

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01412</u>		QUAL. ENG. N. PANDA		
S/N <u>1548-22</u>		REVISED BY J. REDMAN 02/05/95		



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.440	8.803							11.794	11.412
L - TOP							1.896	2.992							1.279	1.620
P - BOTTOM							1.730	2.065							1.280	1.123

NOTE: NOT TO SCALE

**Appendix C:**  
**Edge Break Data for Strap Pack 1174**

INTENTIONALLY LEFT BLANK.

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01442</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1174-1</u>		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.224	10.670							10.851	10.867
L - TOP							2.062	1.995							1.794	1.766
P - BOTTOM							2.170	1.820							1.969	1.874

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01430		DUAL. ENG. N. PANDA	09/06/86	
S/N 1174-2		REVISED BY J REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16		
FLATNESS							9.431	10.856								10.508	10.747	
L - TOP								2.576	1.820								1.766	1.745
P - BOTTOM								2.476	1.809								2.158	1.854

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 6	REV. NO. E
THICKNESS 0.01429		QUAL. ENG. N. PANDA		
S/N 1174-3		REVISED BY J REDMAN 09/05/95		

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.897	10.04							10.141	10.202
L - TOP							2.387	2.158							2.138	2.633
P - BOTTOM							2.305	2.158							2.212	1.565

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS <b>0.01422</b> S/N <b>1174-4</b>		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.199	9.929							10.703	10.278
L - TOP							2.965	2.267							1.983	1.929
P - BOTTOM							2.212	2.049							1.874	2.107

NOTE: NOT TO SCALE

SUPP NO. QO2	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01428		QUAL. ENG. N. PANDA 09/06/86		
S/N 1174-5		REVISED BY J REDMAN 09/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS RECD	.008 MIN
III, IV	EDGEBREAK RECD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS						9182	9803							9986	8785	
L - TOP						2845	2453							2267	2768	
P - BOTTOM						2496	2187							2170	2833	

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 0006	REV. NO. E
THICKNESS 0.01428		QUAL. ENG. N. PANDA 09/06/86		
S/N 1174-6		REVISED BY J REDMAN 09/05/95		


I	LAMINATE THICKNESS .014+- .0007														
II	FLATNESS REQD .008 MIN														
III, IV	EDGEBREAK REQD .001 MIN														

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.151	10.141							10.695	10.444
L - TOP							2.212	2.212							1.874	1.918
P - BOTTOM							2.158	2.116							1.883	2.158

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01448</u>		DUAL. ENG. N. PANDA	09/06/86	
S/N <u>1174-7</u>		REVISED BY J. REDMAN	09/05/95	




I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.276	9.286							10.225	9.984
L - TOP							2.857	2.791							1.766	2.399
P - BOTTOM							2.147	2.441							2.387	2.116

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF page 6	REV. NO. E
THICKNESS <b>0.01423</b>		QUAL. ENG. N. PANDA 09/06/86		
S/N <b>1174-8</b>		REVISED BY J. REDMAN 02/05/95		




I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.938	9.203							9.136	8.392
L - TOP							3.008	2.640							2.942	3.128
P - BOTTOM							2.670	2.531							2.267	2.953

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01425</b>		QUAL. ENG. N. PANDA 09/06/86		
S/N <b>1174-9</b>		REVISED BY J REDMAN 02/05/95		



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.938	9.145							9.875	10.717
L - TOP							3.028	2.507							2.224	1.690
P - BOTTOM							2.441	2.585							2.507	1.887

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01424</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1174-10</u>		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							8.458	10.043							8.863	9.265
L - TOP							2.942	2.878							2.628	2.561
P - BOTTOM							2.854	2.441							2.710	2.540

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS <b>0.01430</b>		DUAL. ENG. N. PANDA 09/06/86		
S/N <b>1174-II</b>		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.635	9.766							9.101	9.278
L - TOP							2.430	2.441							2.885	2.768
P - BOTTOM							2.453	2.224							2.561	2.427

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01435 S/N 1174-12		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 02/05/95		



I LAMINATE THICKNESS .014+- .0007

II FLATNESS REQD .008 MIN

III, IV EDGEBREAK REQD .001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.603	9.504							10.393	10.779
L - TOP							2.485	2.942							1.969	1.658
P - BOTTOM							2.485	2.212							2.130	1.954

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01425</b> S/N <b>1174-13</b>		QUAL. ENG. N. PANDA REVISED BY J. REDMAN 02/05/95 09/06/86		


I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.515	9.744								10.573 9.003
L - TOP							2.471	2.158								1.983 3.455
P - BOTTOM							2.642	2.466								2.062 1.941

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01420</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1174-14</u>		REVISED BY J REDMAN 09/05/95		



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.042	9.703							9.856	9.723
L - TOP							2.496	2.430							2.291	2.763
P - BOTTOM							2.103	2.278							2.237	2.166

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF page 6	REV. NO. E
THICKNESS <u>0.01425</u> S/N <u>1174-15</u>		QUAL. ENG. N. PANDA REVISED BY J. REDMAN 09/06/86 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.689	9.585								10.504
L - TOP							2.399	2.768								1.864
P - BOTTOM							2.430	2.125								2.049

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF page 6	REV. NO. E
THICKNESS <u>0.01432</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>1174-16</u>		REVISED BY J. REDMAN	02/05/95	



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.646	9.703							10.659	10.638
L - TOP							2.682	2.594							1.658	1.537
P - BOTTOM							2.345	2.376							2.345	2.412

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01425</u>		QUAL. ENG. N. PANDA		
S/N <u>1174-17</u>		REVISED BY J. REDMAN 02/05/95		


I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.434	9.651								10.836	11.041
L - TOP							2.092	2.267								1.973	1.833
P - BOTTOM							1.995	2.461								1.887	1.671

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01424</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>1174-18</u>		REVISED BY J. REDMAN	02/05/95	




POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.986	9.429							10.638	10.694
L - TOP							2.158	2.485							2.076	1.779
P - BOTTOM							2.224	2.427							1.766	2.076

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01423</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>1174-19</u>		REVISED BY J. REDMAN	09/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.723	9.246							10.270	9.981
L - TOP							2.332	2.649							2.278	2.496
P - BOTTOM							2.321	2.749							1.995	1.841

NOTE: NOT TO SCALE

**THICKNESS** 0.01425  
**S/N** 1174-20

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							9.037	9.145								10.379	9.515
L - TOP							2.441	2.803								1.983	1.995
P - BOTTOM							2.791	2.453								2.183	3.128

**NOTE: NOT TO SCALE**

[illegible]

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01420		QUAL. ENG. N. PANDA 09/06/86		
S/N 1174-21		REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS .014+- .0007														
II	FLATNESS REQD .008 MIN														
III, IV	EDGEBREAK REQD .001 MIN														

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							9.526	10.235								9.572	10.224
L - TOP							2.278	1.820								2.845	2.183
P - BOTTOM							2.345	2.376								2.103	1.929

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. F
THICKNESS <u>0.01420</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>1174-22</u>		REVISED BY J REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.398	10.460								10.290	10.201
L - TOP							2.235	2.116								2.359	1.820
P - BOTTOM							1.995	1.954								1.901	2.252

NOTE: NOT TO SCALE

**Appendix D:**

**Edge Break Data for Randomly Selected  
Strap Pack Laminates  
From Packs 1167–1177 and Two “Extra” Laminates**

INTENTIONALLY LEFT BLANK

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of pages 6	REV. NO. E
THICKNESS 0.01445		QUAL. ENG. N. PANDA		
S/N 1167-1		REVISED BY J. REDMAN 09/05/95		

VIDEO SCREEN


I	II	III	IV
LAMINATE THICKNESS	.014+- .0007		
FLATNESS REQD	.008 MIN		
EDGEBREAK REQD	.001 MIN		

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							9.850	10.167								10.242	10.783
L - TOP							2.185	2.352								2.278	2.075
P - BOTTOM							2.750	1.976								1.909	1.704

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01440</b>		QUAL. ENG. N. PANDA	09/06/86	
S/N <b>1167-8</b>		REVISED BY J REDMAN	09/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.630	10.492							10.492	10.423
L - TOP							2.147	2.072							2.138	2.019
P - BOTTOM							2.531	1.854							2.083	2.075

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01440		QUAL. ENG. N. PANDA 09/06/86		
S/N 1167-20		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.646	9.575							9.025	11.028
L - TOP							2.441	2.605							2.791	1.626
P - BOTTOM							2.453	2.202							2.682	1.973

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01455</b> S/N <b>1168-3</b>		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.558	9.657							9.588	10.555
L - TOP							2.198	2.453							2.794	1.954
P - BOTTOM							1.779	2.704							2.252	2.008

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01435</b> S/N <b>1168-12</b>		DUAL. ENG. N. PANDA REVISED BY J REDMAN 09/06/86 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.714	10.729								10.985
L - TOP							1.929	1.916								1.887
P - BOTTOM							1.874	1.954								1.645

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01430</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1168-20</u>		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.630	10.061							9.754	10.073
L - TOP							2.461	2.224							2.550	2.412
P - BOTTOM							2.259	1.983							2.038	2.076

NOTE: NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 OF Page 6	REV. NO. E
THICKNESS <u>0.01440</u>		QUAL. ENG. N. PANDA	09/06/86	
S/N <u>1169-13</u>		REVISED BY J REDMAN	02/05/95	

I	LAMINATE THICKNESS	.014 ± .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGE BREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.238	10.426								10.096	10.882
L - TOP							2.336	1.675								2.376	1.635
P - BOTTOM							2.059	2.510								2.038	2.028

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 20	REV. NO. F
THICKNESS <u>0.01435</u> S/N <u>1169-22</u>		QUAL. ENG. N. PANDA REVISED BY J REDMAN 09/06/86 02/05/95		


I	LAMINATE THICKNESS .014+- .0007															
II	FLATNESS REQD .008 MIN															
III.IV	EDGEBREAK REQD .001 MIN															

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.257	10.902								9.824	10.270
L - TOP							2.350	1.945								2.412	2.212
P - BOTTOM							1.957	1.786								2.138	1.983

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01435</b>		QUAL. ENG. N. PANDA		
S/N <b>1172-7</b>		REVISED BY J. REDMAN 02/05/95		



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							9.948	10.338								10.523 11.522
L - TOP							2.223	2.168								2.183 1.580
P - BOTTOM							2.233	2.001								1.941 1.470

NOTE NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01440 S/N 1172-16		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 09/05/95		

I	LAMINATE THICKNESS .014+- .0007															
II	FLATNESS REOD .008 MIN															
III, IV	EDGEBREAK REOD .001 MIN															

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.426	10.972								10.495	11.308
L - TOP							1.967	1.841								2.185	1.626
P - BOTTOM							2.295	1.730								1.407	1.690

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01435</b> S/N <b>1172-21</b>		QUAL. ENG. N. PANDA REVISED BY J. REDMAN 09/06/86 09/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.223	10.396								10.873
L - TOP							2.223	1.737								1.786
P - BOTTOM							2.003	2.185								1.730

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E
THICKNESS 0.01435		DUAL. ENG. N. PANDA 09/06/86		
S/N 1173-2		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGE BREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.159	9.766							10.747	11.174
L - TOP								2.118	2.344						1.792	1.635
P - BOTTOM								2.178	2.302						1.847	1.580

NOTE NOT TO SCALE



SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 6	REV. NO. E
THICKNESS <u>0.01425</u>		QUAL. ENG. N. PANDA 09/06/86		
S/N <u>1173-19</u>		REVISED BY J REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014 +- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN


  

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.459	10.546								10.572 10.573
L - TOP							1.730	1.896								2.240 2.147
P - BOTTOM							2.130	2.130								1.682 1.754

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <b>0.01445</b>		QUAL. ENG. N. PANDA 09/06/86		
S/N <b>1175-1</b>		REVISED BY J REDMAN 02/05/95		



POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.155	8.559							10.354	9.622
L - TOP							2.168	2.890							2.013	2.728
P - BOTTOM							2.223	3.057							2.165	2.223

NOTE NOT TO SCALE


SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of Page 6	REV. NO. E.
THICKNESS 0.01425		QUAL. ENG. N. PANDA 09/06/86		
S/N 1175-12		REVISED BY J REDMAN 02/05/95		

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
POSITION NO.															
FLATNESS						10.307	10.458								10.754
L - TOP						2.178	1.957								1.952
P - BOTTOM						2.063	1.957								1.602

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. E
THICKNESS 0.01435		DUAL. ENG. N. PANDA	09/06/86	
S/N 1175-19		REVISED BY J REDMAN	02/05/95	



I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.115	10.337							10.144	10.389
L - TOP							1.864	2.057							2.244	2.409
P - BOTTOM							2.441	1.945							2.178	1.675


NOTE: NOT TO SCALE



SUPP NO. Q02 PART NAME LAMINATE SET-TAIL ROTOR PART NO. 7-211421023-9 OPERATION #20 REV. NO. E

THICKNESS 0.01435 S/N 1176-3

QUAL. ENG. N. PANDA 09/06/86  
 REVISED BY J. REDMAN 02/05/95



I LAMINATE THICKNESS .014+- .0007  
 II FLATNESS REQD .008 MIN  
 III, IV EDGEBREAK REQD .001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.306	10.469								11.532 10.370
L - TOP							1.973	2.284								1.654 2.496
P - BOTTOM							2.267	1.730								1.620 1.690

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01435</u> S/N <u>1176-10</u>		DUAL. ENG. N. PANDA 09/06/86 REVISED BY J. REDMAN 02/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.430	10.833								11.07	10.550
L - TOP							2.075	1.847								1.737	1.874
P - BOTTOM							2.092	1.896								1.841	2.103

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E													
THICKNESS 0.01435		QUAL. ENG. N. PANDA															
S/N 1176-21		REVISED BY J REDMAN 09/06/86															
POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.681	11.552								10.005	11.705
L - TOP							1.745	1.607								2.523	1.830
P - BOTTOM							2.092	1.515								2.038	1.520
NOTE: NOT TO SCALE																	

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01435		DUAL. ENG. N. PANDA	09/06/86	
S/N 1177-5		REVISED BY J REDMAN	09/05/95	

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.170	10.016								10.470	10.997
L - TOP							2.147	2.376								2.247	1.712
P - BOTTOM							2.092	2.321								1.655	1.833

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of 00086	REV. NO. F
THICKNESS 0.01435		QUAL. ENG. N. PANDA 09/06/86		
S/N 1177-11		REVISED BY J REDMAN 02/05/95		


I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGE BREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							10.010	10.720								11.164	10.568
L - TOP							2.295	2.138								1.902	2.028
P - BOTTOM							2.130	1.690								1.339	1.864

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01445		DUAL. ENG. N. PANDA	09/06/86	
S/N 1177-17		REVISED BY J. REDMAN	02/05/95	




I	LAMINATE THICKNESS	.014 + -.0007
II	FLATNESS REOD	.008 MIN
III, IV	EDGEBREAK REOD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							10.596	10.838								11.349
L - TOP							1.896	2.240								1.580
P - BOTTOM							2.068	1.454								1.571
																1.864

NOTE: NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS 0.01450		QUAL. ENG. N. PANDA	09/06/86	
S/N EXTRA-1		REVISED BY J REDMAN	02/05/95	



- I LAMINATE THICKNESS .014+- .0007
- II FLATNESS REQD .008 MIN
- III, IV EDGEBREAK REQD .001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FLATNESS							13.983	13.987							13.884	13.902
L - TOP							0.218	0.276							0.279	0.226
P - BOTTOM							0.137	0.234							0.163	0.158

NOTE NOT TO SCALE

SUPP NO. Q02	PART NAME LAMINATE SET-TAIL ROTOR	PART NO. 7-211421023-9	OPERATION #20 of page 6	REV. NO. E
THICKNESS <u>0.01430</u> S/N <u>EXTRA-2</u>		QUAL. ENG. N. PANDA REVISED BY J REDMAN 09/06/86 09/05/95		

I	LAMINATE THICKNESS	.014+- .0007
II	FLATNESS REQD	.008 MIN
III, IV	EDGEBREAK REQD	.001 MIN

POSITION NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
FLATNESS							13.402	13.874								13.687	13.874
L - TOP							0.352	0.310								0.176	0.219
P - BOTTOM							0.287	0.295								0.381	0.237

NOTE: NOT TO SCALE



NO. OF  
COPIES ORGANIZATION

- 2 DEFENSE TECHNICAL  
INFORMATION CENTER  
DTIC DDA  
8725 JOHN J KINGMAN RD  
STE 0944  
FT BELVOIR VA 22060-6218
- 1 HQDA  
DAMO FDQ  
D SCHMIDT  
400 ARMY PENTAGON  
WASHINGTON DC 20310-0460
- 1 OSD  
OUSD(A&T)/ODDDR&E(R)  
R J TREW  
THE PENTAGON  
WASHINGTON DC 20301-7100
- 1 DPTY CG FOR RDE HQ  
US ARMY MATERIEL CMD  
AMCRD  
MG CALDWELL  
5001 EISENHOWER AVE  
ALEXANDRIA VA 22333-0001
- 1 INST FOR ADVNCD TCHNLGY  
THE UNIV OF TEXAS AT AUSTIN  
PO BOX 202797  
AUSTIN TX 78720-2797
- 1 DARPA  
B KASPAR  
3701 N FAIRFAX DR  
ARLINGTON VA 22203-1714
- 1 NAVAL SURFACE WARFARE CTR  
CODE B07 J PENNELLA  
17320 DAHLGREN RD  
BLDG 1470 RM 1101  
DAHLGREN VA 22448-5100
- 1 US MILITARY ACADEMY  
MATH SCI CTR OF EXCELLENCE  
DEPT OF MATHEMATICAL SCI  
MAJ M D PHILLIPS  
THAYER HALL  
WEST POINT NY 10996-1786

NO. OF  
COPIES ORGANIZATION

- 1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL DD  
J J ROCCHIO  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145
- 1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CS AS (RECORDS MGMT)  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145
- 3 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CI LL  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145
- ABERDEEN PROVING GROUND
- 4 DIR USARL  
AMSRL CI LP (305)

NO. OF  
COPIES ORGANIZATION

2 DIRECTOR  
US ARMY AMCOM(P)  
AMSAT AR EF  
KIRIT BHANSALI  
BLDG 8027  
REDSTONE ARSENAL AL  
35898-5093

ABERDEEN PROVING GROUND

10 DIR USARL  
AMSRL WM MD  
S GRENDahl  
BLDG 4600

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1999	3. REPORT TYPE AND DATES COVERED Final, Mar 96 - Apr 97
4. TITLE AND SUBTITLE The Metallurgical Examination and Inspection of Apache Tail Rotor Strap Pack Laminates and Assemblies			5. FUNDING NUMBERS  N/A
6. AUTHOR(S)  Scott M. Grendahl			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-MD Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER  ARL-TR-2018
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) ATCOM 4300 Goodfellow Blvd. St. Louis, MO 63120-1798			10. SPONSORING/MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words)  The U.S. Army Research Laboratory-Weapons and Materials Research Directorate (ARL-WMRD) performed a dimensional inspection and metallurgical investigation of AH-64 Apache tail rotor strap pack assemblies and individual laminate sets. All of the dimensional critical characteristics were examined in an attempt to determine the cause of a buckling phenomenon within the strap pack assemblies. Conformance to the manufacturer's governing specifications with respect to the material, heat treatment, and marking requirements was also investigated. The cause of the buckling was attributed to a combination of factors. Dimensional nonconformances were identified. Most of the hole diameters were found to be well below the specified range, causing the assemblies to be forced together. Transposition of the laminates during manufacture was also highly likely to have occurred, adding to the misalignment of the assembly. All other characteristics of the laminates and assemblies were found to conform to the governing part drawings and specifications.			
14. SUBJECT TERMS AM-355, dimensional inspection, strap pack, metallurgy			15. NUMBER OF PAGES 124
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL

INTENTIONALLY LEFT BLANK.

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-2018 (Grendahl) Date of Report July 1999
2. Date Report Received \_\_\_\_\_
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

Organization

Name

E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
**(DO NOT STAPLE)**